

# 12.8V9Ah








**LFP Li-ion Battery** 



# **Dimension:**



# **SAFETY**

- Cylindrical LiFePO4 cells (21700-3Ah), High consistency, long cycle life and much more safety.
- UN38.3, CE certification for system.
- The cycle life over 2000 times @80%DOD

# **DESIGN**

- ABS container, replace VRLA battery perfectly.
- Fast charge performance.
- -20~+55° C widely temperature range.
- Maintenance free.

### **BATTERY MANAGEMENT SYSTEM (BMS)**

- + Integrated hardware BMS inside.
- Independent protection for charge and discharge.
- Over voltage, low voltage, over temperature and short circuit protection.

Unit: mm



# **Li-ion Battery**

# 12.8V9Ah

# Specification

Model	R-LFP12.8V9Ah
Part Number	8010128000901
Nominal Voltage [V]	12.8
Nominal Capacity [Ah]	9
Total Energy [Wh]	115.2
Max. Charging Current [A]	9
Recommended Charging Current [A]	4.5
Charging Voltage [V]	14.6
Max. Discharging Current [A]	9
End of Dicharge Voltage [V]	11.2
Pulse Discharge Current	12A @ 10s
Dimension [W*D*H, mm]	151*65*93.5
Weight [Kg]	1.10
Operation Humidity	0~95% RH (No condensing)
Operating Temperature Range	Charge: 0 ~ +50 $^{\circ}$ C; Discharge: -20 ~ +55 $^{\circ}$ C
BMS Protection	Over charge Over discharge, Over temperature, Short circuit
Parallel Support	Yes, Max 2 Sets
Series Support	Yes, Max 4 Sets
Cycle Life	>2000
Designed Calendar Life	>10 Years
Certification	UN38.3, CE, MSDS

1. 80% DOD and to 80% of initial capacity.

The datasheet is subject to change without prior notification

For more information, contact with: sales@ritarpower.com

Hengyang Ritar Power Co., Ltd. Hengyang Rich Power Co., Ltd.

No.1 Huagong Road, Songmu Industrial Park, Shigu District, Hengyang, Hunan, 421001, China